

# Innovative New POC with the Established Reliability of the Oxlife Independence<sup>®</sup>

- Remote Monitoring via Cellular Connectivity and DNA Technology<sup>®</sup>
- Efficient Performance and Longer Battery Life with Energy Smart Technology<sup>®</sup>
- Lightweight and Durable
- Simple Control Functions with LCD Screen
- Battery Chargeable While Unit in Operation



OXLIFE  
**FREEDOM<sup>®</sup>**



1-877-774-9271 | [www.oxygenconcentratorstore.com](http://www.oxygenconcentratorstore.com)

## PRODUCT SPECIFICATIONS<sup>1</sup>

<b>Dimensions</b>	Height: 9.4" • Width: 9.0" • Depth: 3.4"
<b>Weight</b>	Device: 4.53 lbs • Battery: 1.35 lbs
<b>Battery Duration</b>	Up to 4.5 hours
<b>Battery Recharge Time<sup>2</sup></b>	2 hours on AC or DC power
<b>Oxygen Concentration</b>	87% - 95% at sea level at all settings
<b>Pulse Flow Settings<sup>3</sup></b>	1 - 5 with bolus size of 10 - 44ML
<b>User Interface</b>	Color LCD screen with keypad controls
<b>AC Power</b>	Universal Input: 100 - 240V, 50/60Hz Output: 24V, 6.3A Maximum Power Consumption: 150W
<b>DC Power</b>	Input: 11.5 - 16V, 18A Max Output: 19V, 6.3A Maximum Power Consumption: 120W
<b>Operating Temperature</b>	50°F (10°C) to 104°F (40°C)
<b>Altitude Operating Range</b>	0 - 13,123 feet (0 - 4,000 meters)
<b>Transportation/Storage Humidity</b>	0 - 95% non-condensing

<sup>1</sup> O2 Concepts® reserves the right to revise specifications at anytime without notice

<sup>2</sup> Battery recharge time will increase if unit is operating on DC power while charging

<sup>3</sup> Bolus size based on 20 breaths per minute



**American Medical Sales and Rentals**  
7032 S Revere Parkway, Suite 320  
Centennial, CO 80112  
Phone: 877-774-9271

[www.oxygenconcentratorstore.com](http://www.oxygenconcentratorstore.com)  
E-mail: [sales@amsrco.com](mailto:sales@amsrco.com)



**1-877-774-9271 | [www.oxygenconcentratorstore.com](http://www.oxygenconcentratorstore.com)**